

# Electronic Lock

# **PRODUCT DESCRIPTION**

The ID LOCK 7000 is an electronic locking system with a convenient combination lock code for the uncomplicated locking of cabinets and valuables compartments. Because it is important to us that your sensitive data and valuables are safe from unauthorized third parties. The ID LOCK 7000 can be installed in wooden cabinet doors as well as in steel furniture. Due to its ergonomic and high-quality design, it is not without reason one of the most practical locking systems on the market.

### **Private mode**

In this mode, the lock is permanently assigned to a single user. This user is now permanently authorized to operate the lock.

#### **Battery warning**

By lighting up a red LED signal light during pin entry, the device indicates the falling battery voltage. It is recommended to change the battery as soon as the lock indicates a low level. If the battery level reaches the critical range, the ID LOCK 7000 cannot be operated.

### Lock mode

If the code is entered incorrectly for the fourth time in a row, the lock is automatically locked for 1 minute. During this time, any attempted pin entry is rejected by the lock.



## **APPLICATIONS**

- Healtcare
- Office building
- Schools & Universities
- · Hotels

## **FEATURES**

- Ergonomic handling and high-quality design
- Battery replacement without removal
- Easy retro fitting, e.g. to replace mechanical lever locks
- · Bolt in 45° steps adjustable
- Emergency power supply via micro USB connection

iDTRONIC GmbH Ludwig-Reichling-Straße 4 67059 Ludwigshafen GERMANY Phone:+49 (0)621 66 900 94-0 Mail: info@idtronic-group.com Web: idtronic-group.com

Subject to change without notice. ©2024 iDTRONIC GmbH



## **TECHNICAL DATA**

- 6	ELECTRICAL SPECIFICATIONS		MECHANICAL SPECIFICATIONS	
E	Bolt type	В	Dimensions	43,3 mm diameter
E	Battery	CR2450 (1×)	Installation dimensions	16 mm x 19 mm
[	Dynamic current	<120 mA	Material	Case: Zamak Front flap: Plastic Latch: Steel
l	Locking direction	Left (90°)		
l	Lock fastening	M19 nut (1x)	Maximum door thickness	18 mm
(	Closing Cycles	3.000	Scope of delivery	1x locking system 1x Bolt fastening screws 1x M19 nut
r	Modes	Private mode Multiuser mode		
F	Pin (default)	1234		
ſ	Mastercode (default)	4321		
1	No. of PINs	max. 1		
1	No. of master codes	max. 1		
F	PIN / master code length	4 to 15 digits		

# ORDER CODES

VERSIONS	ORDER CODES
ID LOCK 7000	R-EA-EEL-7000



## **PRODUCT PICTURES**

2

**FRONT VIEW** 



**REAR VIEW** 

SIDE VIEW



ACCESSORIES



iDTRONIC GmbH Ludwig-Reichling-Straße 4 67059 Ludwigshafen GERMANY Phone:+49 (0)621 66 900 94-0 Mail: info@idtronic-group.com Web: idtronic-group.com

Subject to change without notice. ©2024 iDTRONIC GmbH