


INDUSTRIAL READER



	DESKTOP READER NEO 2	CANBUS IGNITE SMART	MID RANGE READER BLUEBOX	CYLINDRICAL READER M30
Frequencies	UHF, HF, LF, LEGIC	HF NFC: 13.56 MHz	UHF (865 - 868 MHz)	UHF (865 - 868 MHz)
Dimensions	115 x 70 x 17 mm	81.4 x 68.6 x 24.1 mm	190 x 190 x 80 mm	M30 x 1.5 x 90.65 mm
Antenna	Integrated			
Reading Distance	Up to 5 m (UHF: up to 15 m)	Up to 3 cm	up to 8 m	up to 40 cm
Power Supply	200 mA	120 mA	10 ... 36 Vdc, PoE	100 mA
Interfaces	USB - Virtual ComPort USB - HID	CANbus (SAE J1939 or CANopen)	M12 Connectors	RS232, RS485, CANbus, CANopen
Connection	120 cm long cable with USB- Type-A plug	JST 04T-JWPF-VSLE-S, 0.33 mm ² /AWG22 wire gauge	RS232 / RS485 Ethernet 10 - 100M Wiegand Canbus (J1939)	5 pin M12 A-coded male connector

INDUSTRIAL READER FAMILY IQBOX (NEW)



	DESKTOP IQBOX	M30 IQBOX	LONG RANGE READER/ ANTENNA IQBOX E4	LONG RANGE READER/ 4CH IQBOX U4
Frequencies	UHF (865 - 868 MHz)	UHF (865 - 868 MHz)	UHF (865 - 868 MHz)	UHF (865 - 868 MHz)
Dimensions			205 x 205 x 70mm	
Antenna	Integrated			4x External
Reading Distance	Up to 30 cm	Up to 30 cm	Up to 10 m	Up to 12 m
Interfaces	USB	RS232 RS485 CANBUS	RS232 / RS485 Ethernet 10–100M CanBus, ModBus, ProfiNET	RS232 / RS485 Ethernet 10–100M CanBus, ModBus, ProfiNET